

ACCESSORIES AND HARDWARE

CRSA, NON-TRACKING RAIN SHEDS

Rain sheds are used as creepage extenders on medium voltage cable termination and insulators in outdoor applications. The recommended number of sheds to be used varies according to the voltage rating of the cable.

VOLTAGE	NUMBER OF SHEDS	
	MM	IN
5 - 8 kV	1	
15 kV	2	
25-28 kV	3	
35 kV	4	

PART NUMBER	CABLE DIAMETER USE RANGE	
	MM	IN
CRSA 37/12	32 - 12	1.26 - 0.47
CRSA 57/25	52 - 25	2.05 - 0.98
CRSA 75/35	70 - 35	2.76 - 1.38



CFS, CONSTANT FORCE SPRINGS

Used for securing ground braids on cable terminations and joints.

PART NUMBER	USE RANGE	
	MM	IN
CFS0405	12.7 - 25.4	0.50 - 1.00
CFS1005	25.4 - 50.8	1.00 - 2.00
CFS1675	42.4 - 76.2	1.67 - 3.00



MESH, TINNED COPPER SHIELDING MESH

Provides shield continuity on shielded power cables.

PART NUMBER	WIDTH		LENGTH	
	MM	IN	M	FT
MESH25015	57.15	2.25	4.57	15



BRDM, TINNED COPPER, MOISTURE BLOCKED GROUND BRAID

Used with cable terminations and joints to provide ground continuity.

PART NUMBER	GAUGE SIZE AWG	WIDTH		LENGTH	
		MM	IN	MM	IN
BRDM0836	8	12.7	0.50	914.4	36
BRDM0636	6	19.5	0.75	914.4	36
BRDM0436	4	25.4	1.00	914.4	36



ACCESSORIES AND HARDWARE

CFGK, FAULT GROUNDING KITS

Kits are designed to provide complete external grounding for tape shield/drain wire terminations.

PART NUMBER	DESCRIPTION
CFGK1X36	One kit contains a constant force spring, copper foil tape and #8 AWG tinned copper braid, 36 in long
CFGK2X36	One kit contains a constant force spring, copper foil tape and #6 AWG tinned copper braid, 36 in long
CFGK3X36	One kit contains a constant force spring, copper foil tape and #4 AWG tinned copper braid, 36 in long



CPK, CABLE PREPARATION KIT

Kits contain all the necessary parts to clean and abrade 1-3/C or 3-1/C and 1/C cable accessories.

PART NUMBER	DESCRIPTION
CPK0306	One kit contains 3 each of solvent wipes, dry wipes and 3 strips of abrasion paper
CPK0102	One kit contains 1 each of solvent wipe, dry wipe and strip of abrasion paper



Or order by adding "P" suffix to MV kit

CTSR, NON-TRACKING RED SEALANT

Heat activated red sealant mastic for use in general purpose, medium voltage applications. Ideal for use in cable terminations and joints.

PART NUMBER	WIDTH		LENGTH		THICKNESS	
	MM	IN	MM	IN	MM	IN
CTSR 021535	53.34	2.10	381	15	1.016	0.040
CTSR 013060	26.67	1.05	762	30	1.524	0.060



GENERAL PURPOSE, HOT-MELT SEALANTS AND MASTIC TAPES

Used for sealing ends of uncoated tubing, molded parts or filling voids.

PART NUMBER	SEALANT COLOUR	DESCRIPTION
CTSG-1	Grey	1 in wide, cross-linked grey butyl mastic tape suitable for continuous high temperature applications. Offered in 25 ft rolls.
CTSB-2	Black	2 in wide, specially designed rubber based black sealant mastic tape for use with heat shrink tubing and molded parts for void-free/watertight sealing and low voltage applications. Offered in 25 ft rolls.



All information contained in this data sheet is believed to be reliable. We advise, however, that customers should separately evaluate the suitability of our products for their particular application. DSG-Canada and ShawCor give no guarantees in respect of the accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product.