

INSULATE
SEAL
PROTECT

>3:1
SHRINK RATIO



HEAT SHRINK CABLE REPAIR SLEEVE

ADHESIVE LINED, HEAT SHRINK WRAPAROUND SLEEVE THAT IS CLOSED WITH A FLEXIBLE STAINLESS-STEEL LOCKING CHANNEL. USED FOR GENERAL RE-JACKETING AND SEALING APPLICATIONS, PROTECTION OF DAMAGED CABLE OR REPAIR OF CABLE JOINTS. INSTALLS EASILY IN SPLICE APPLICATIONS THAT ARE LONGER IN LENGTH

FEATURES AND BENEFITS

- >3:1 shrink ratio
- Provides water tight seal upon recovery
- Offers mechanical durability
- Application procedure is quick, simple and clean
- Covered with thermochromatic paint that changes upon correct shrink temperature
- Sleeve and channel can be cut to suit short application requirements
- Steel channel provides permanent closure system
- Installation temperature range: -15°C to 45°C

TYPICAL APPLICATIONS

- Cable jacket repair
- Primary insulation cover on low voltage cables
- Re-jacketing cover for power cables



DIMENSIONS

ORDER NUMBER	EXPANDED ID		RECOVERED ID		RECOVERED WALL THICKNESS		SLEEVE LENGTH	
	MM	IN	MM	IN	MM	IN	MM	IN
CRDW-1	43	1.69	8	0.32	2.3	0.09	1219	48
CRDW-2	75	2.95	15	0.59	2.3	0.09	1219	48
CRDW-3	93	3.66	25	0.98	2.3	0.09	1219	48
CRDW-4	137	5.39	34	1.34	2.3	0.09	1219	48
CRDW-5	160	6.30	48	1.89	2.3	0.09	1219	48
CRDW-6	200	7.87	48	1.89	2.3	0.09	1219	48

ORDERING

- Select a dimension which will shrink snugly over the component to be covered. Allow for a minimum of 76 mm (3 in) length overlap beyond each end of the area to be covered.
- Please specify the product name plus the options you require
- Order Example: CRDW-1
- Standard Product: Black, 48 in length

Please contact your Customer Service Representative for information on custom lengths and material data sheet.

All information contained in this data sheet is believed to be reliable. We advise, however, that customers should separately evaluate the suitability of our products for their particular application. DSG-Canusa and ShawCor give no guarantees in respect of the accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product.