

INSULATE
SEAL
PROTECT

3:1
SHRINK RATIO



STREET LIGHTING KIT

STREET LIGHTING KITS ARE A CONVENIENT METHOD FOR THE INSTALLATION, MAINTENANCE AND REPAIR OF STREET LIGHTING SYSTEMS

FEATURES AND BENEFITS

- 3:1 shrink ratio
- Excellent insulation, sealing and strain relief for splice repairs or cable extensions
- Thermoplastic adhesive liner provides complete environmental protection and insulation
- High impact and abrasion resistance
- Kits can be installed at temperature as low as -40°C
- Tubing will not split or rupture during normal installation, even when overheated
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 120°C

TYPICAL APPLICATIONS

- Street lighting cable splices



DIMENSIONS

ORDER NUMBER	KIT DESCRIPTION	CONNECTOR TYPE
1	12 AWG, 2 Conductor, Solid 10 AWG, 2 Conductor, Stranded	2 each, "C" Type/Crimp
1A	12 AWG, 2 Conductor, Solid 10 AWG, 2 Conductor, Stranded (with ground)	3 each, "C" Type/Crimp

CONTENTS

- Each kit includes adhesive coated heat shrink sleeves and compression connectors

ORDERING

- Select the appropriate CSLK Street Lighting Kit.
- Please specify the product name plus the options you require.
- Order Example: CSLK 1A

Please contact your Customer Service Representative for information on custom kits and material data sheet.

All information contained in this data sheet is believed to be reliable. We advise, however, that customers should separately evaluate the suitability of our products for their particular application. DSG-Canusa and ShawCor give no guarantees in respect of the accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product.