

INSULATE
SEAL
PROTECT

HEAT SHRINK TORCHES AND GUNS

HEAVY DUTY TORCHES PROVIDING CLEAN BURNING, VARIABLE POSITION SHRINK CAPABILITY. IDEAL FOR SHRINKING MEDIUM AND HEAVY WALL PRODUCTS

BASIC TORCH KITS WITHOUT AUTOMATIC IGNITION

CTCH-BHSC-04

Light weight Sievert portable torch kit ideal for installation of low voltage electrical and CATV splice applications. Kit contains torch handle, 20,000 BTU/hr soft flame burner and 4 ft hose regulator assembly for 14.1 or 16.4 oz disposable propane cylinders.



CTCH-BHSC-25

Light weight Sievert portable torch kit ideal for installation of medium and heavy wall heat shrink products. Kit contains torch handle, 40,000 BTU/hr soft flame burner, 25 ft hose, adjustable P.O.L. regulator for refillable propane cylinders.



AUTOMATIC SAFETY TORCH SYSTEM WITH BUILT-IN ON/OFF CAPABILITY

CTCH-CATVO-04

Light weight Siever-Matic S portable torch kit ideal for installation of low voltage electrical and CATV splice applications. Kit contains ergonomic torch handle, 20,000 BTU/hr soft flame burner and 4 ft hose regulator assembly for 14.1 or 16.4 oz disposable propane cylinders.



CTCH-HSK1-00

Light weight Siever-Matic S portable torch kit ideal for installation of medium and heavy wall heat shrink products. Kit contains ergonomic torch handle, 40,000 BTU/hr soft flame burner. Hose and regulator required; can be purchased separately.



CTCH-1

Torch kit with 1 to 20 inch thread screws directly on to standard 14.1 or 16.4 oz disposable tanks or may be attached to propane hose with adapter. Burns propane or MAPP gas.

ACCESSORIES

- CTCH-3334-90: 6,100 BTU/hr hot air burner ideal for low voltage electrical and CATV applications where an open flame is not desirable. This burner can be used with Seiver-Matic S handles in CTCH-CATVO-04 and CTCH- HSK1- 00.
- CTCH-3015-04: 4 ft hose regulator assembly for disposable propane cylinder for CTCH- HSK1- 00
- CTCH-3062-93: Adjustable regulator 28-57 psi for refillable P.O.L. propane cylinder
- CTCH-1510IS: 10 ft hose with 9/16 - 18 LH treads both ends
- CTCH-1525IS: 25 ft hose with 9/16 - 18 LH threads both ends

ELECTRONICALLY CONTROLLED HEAT GUN

CHGN

This ruggedly designed, electronically controlled heat gun is ideal for situations where flame is prohibited. CHGN features a three stage operation with 1500 W output, low noise operation <70 dB (A) providing a continuously variable temperature range of 120 to 1100°F, ample for heat shrinking applications

UL and CSA Listed

